RV PRODUCT DATA SHEETOEM:2088-403-144 (Aqua-King)AFTERMARKET:N/A

APPLICATION

Multi-fixture RV fresh water installations. Other uses may include

12V DC pressurized water systems in cabins. This pump may be used for general fresh water transfer.

PUMP:

Туре:	3 Chamber Diaphragm
Ports:	1/2"-14 NPSM-Male.
Liquid:	130 ℉ [54 ℃] Max
Dry-Prime:	9 feet [2.7 M]
Inlet PSI:	30 PSI [2.1 Bar] Max
Run Dry:	Yes

ELECTRICAL:

Motor:	12VDC Permanent Magnet, Intermittent Duty
Protection:	Thermal Overload, Automatic Restart
Leads:	16 AWG, 16" [40 cm] Red +, 13" [33 cm] Black -
Fuse:	10 Amp Recommended
Control:	Adjustable Switch. Shut-Off 45 PSI [3.1 Bar] ± 5 PSI
	[0.4Bar] Restart 25 PSI [1.8 Bar] ± 5 PSI [0.4 Bar]

MATERIALS:

Housing:	Polypro
Valves:	EPDM
Diaphragm:	Santoprene
Hardware:	Zink Plated Steel

APPROVALS:

c-UL

SHIPPING:

 Net Weight:
 5 Lb [2.3 Kg] each

 Carton Quantity:
 6

 Carton Weight:
 30 Lb [13.6 Kg]

 Carton Size:
 24"L x 18"W x 5"H


 [60.9cm x 45.7cm x 12.7cm]


RELATED DOCUMENTS:

Catalog:	MS-030-138
Installation Manual:	911-352
Applications Spec Guide:	MS-020-005



These legendary pumps have set the standard for the RV Industry. SHURflo 2088 pumps are equipped to deliver high performance and reliability every time they are used. SHURflo potable water pumps operate three independent pumping chambers which allow the pump to self-prime and lift water up to 12 feet. With smooth flow and uninterrupted operation, the Classic[™] Series pumps include a built-in check valve to prevent back flow into the tank. Each pump features an adjustable switch and the capacity to run dry without damage to the pump or motor.





SHURflo reserves the right to update specifications, prices or make substitutions without notice.





Anschrift Liberty Vertriebs GmbH Bonner Straße 103 40589 Düsseldorf Kontakt Tel.: 0211-753520 Fax: 0211-753575 Email: verkauf@libertyshop.de Internet www.libertyshop.de