	EV9612-22 i2000 ² Filter Ca	rtridge
Delivers premium quality water for	ice applications	
	i2000 ² Replacement Cartridge: EV9612-22	BENEFITS New and improved Micro - Pure II media with AgION™ antimicrobial protection inhibits any potential bacterial growth Reduces water - related ice machine problems caused by scale build- up from dirt and dissolved minerals Reduces chlorine taste and odor and other offensive contaminants Self - contained scale inhibitor feed keeps ice machines functioning at full capacity Reduces maintenance and service costs by reducing scale and clogging of distribution lines, evaporator plate and pump Precoat submicron technology reduces dirt and particles as small as 1/2 micron in size and reduces health contaminants such as asbestos fibers and Cryptosporidium and Giardia cysts Sanitary cartridge replacement is simple, quick and clean. Internal filter parts are never exposed to handling or contamination NSF Certified under NSF/ANSI Standards 42
INSTALLATION TIPS	OPERATION TIPS	A P P L I C A T I O N / S I Z I N G
Install vertically with cartridge hanging down Allow 2-1/2" clearance below the cartridge for easy cartridge replacement Flush cartridge by running water through system for five minutes at full flow	Change cartridges on a regular 6 month preventative maintenance program Change cartridges when capacity is reached or when pressure falls below 10 psi Always flush the filter cartridge at time of installation and cartridge change	For ice machine applications Rated Capacity: 9,000 gallons (34,068L)

i2000² Filter Cartridge

18.75"

SPECIFICATIONS

Overall Dimensions: 20.75"H x 3.25"Diameter

Service Flow Rate: Maximum 1.67 gpm (6.3 Lpm)

Rated Capacity: 9,000 gallons

Pressure Requirements: 10 - 125 psi (0.7 – 8.6 bar), non-shock

Temperature: 35 - 100°F (2 - 38°C)

No electrical connection required

The contaminants or other substances removed or reduced by this drinking water system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used with disinfected water that may contain filterable cysts.



Everpure water treatment systems (excluding replaceable elements) are covered by a limited warranty against defects in material and workmanship for a period of five years after date of purchase. Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Everpure will provide a copy of the warranty upon request.



System Tested and Certified by NSF International against NSF/ANSI Standard 42 and 53 for the reduction of:

Standard No. 42: Aesthetic Effects Chemical Unit Taste and Odor Reduction Chlorine Reduction Mechanical Filtration Unit Particulate Reduction, Class I: 99.9+% reduction of particles one-half micron and larger in size Standard No. 53: Health Effects Mechanical Filtration Unit Turbidity Reduction Cyst Reduction Asbestos Reduction





Liberty Vertriebs GmbH Bonner Straße 103 Tel.: 0211-753520 40589 Düsseldorf Fax.: 0211-753575

Internet: www.libertyshop.de Email: verkauf@libertyshop.de