

i4000² Filter Cartridge

23.13

SPECIFICATIONS

Overall Dimensions: 25"H x 3.25"Diameter

Service Flow Rate: Maximum 1.67 gpm (6.3 Lpm)

Rated Capacity: 12,000 gallons

Pressure Requirements: 10 - 125 psi (0.7 – 8.6 bar), non-shock

Temperature: 35 - 100°F (2 - 38°C)

No electrical connection required

The contaminants or other substances removed or reduced by this drinking water system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used with disinfected water that may contain filterable cysts.



Everpure water treatment systems (excluding replaceable elements) are covered by a limited warranty against defects in material and workmanship for a period of five years after date of purchase. Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Everpure will provide a copy of the warranty upon request.



System Tested and Certified by NSF International against NSF/ANSI Standard 42 and 53 for the reduction of:

Standard No. 42: Aesthetic Effects Chemical Unit Taste and Odor Reduction Chlorine Reduction Mechanical Filtration Unit Particulate Reduction, Class I: 99.9+% reduction of particles one-half micron and larger in size

Standard No. 53: Health Effects Mechanical Filtration Unit Cyst Reduction



Liberty Ersatzteile & Zubehör

Liberty Vertriebs GmbH Bonner Straße 103 40589 Düsseldorf

 Tel.: 0211-753520
 Internet: www.libertyshop.de

 Fax:: 0211-753575
 Email: verkauf@libertyshop.de